

20" VESTAL CASTING WITH 12" LID  
LETTERED " SEWER CLEAN OUT "  
OR APPROVED EQUAL

FINAL GRADE

6" PVC CAP

MIN. 1" AND MAX. 4"  
CLEARANCE FROM TOP  
OF CAP TO BOTTOM OF  
CASTING

HDPE PIPE TO EXTEND  
MIN. 3" ABOVE STONE

6" CLEARANCE FROM  
TOP OF PIPE TO TOP  
OF #8 STONE

20" DIAMETER FRATCO  
HDPE METER PIT 7.2 LBS./FT.  
OR EQUAL

6" SDR 35 PVC PIPE

TRACER WIRE

6" MIN. (TYP.)

(6"X6"X6") TEE-WYE

6" SEWER LATERAL

**NOTES:**

1. FOR USE WITH GRASS OR  
LANDSCAPED AREAS BEYOND  
THREE FEET OF BUILDING.

2. CASTING SHALL BE  
INSTALLED SO THAT IT DOES  
NOT CONTACT THE LATERAL OR  
LATERAL CAP.

FLOW

6" FROM TOP OF PIPE TO BOTTOM  
OF METER PIT. CONTRACTOR SHALL  
NOT ALLOW METER PIT TO CONTACT  
LATERAL/TEE-WYE.

City of Carmel Utilities  
Standard Details

Title: TYPE III CLEANOUT  
DETAIL

Date: January 2016

Scale: Not To Scale

Drawing: CS 20

Page 29